INVERTER

SLIM DUCT

Model: ARYG18LLTB

۲

۲











Slim design

The slim design allows installations where ceilings are narrow. Drain hose as standard accessory



Flexible installation

2-type installation methods of ceiling concealed and floor concealed can be selected.

Ceiling concealed

Specifications

Model No.	Indoor unit		ARYG18LLTB
	Outdoor unit		A0YG18LBCB
Power Source		V/Ø/Hz	230/1/50
Capacity	Cooling (Min-Max)	kW	5.20
		BTU/h	17,700(3,100-20,100)
	Heating	kW	6.00
	(Min-Max)	BTU/h	20,500(3,100-25,600)
Input Power	Cooling/Heating	kW	1.62/1.66
EER	Cooling	W/W	3.21
COP	Heating		3.61
Running Current	Cooling/Heating	A	7.2/7.4
Moisture Removal		l/h	2.0
Sound Pressure Level (Cooling/Heating)	Indoor (High)	dB(A)	32
	Outdoor		50/50
Airflow Rate (High) (Cooling/Heating)	Indoor	m³/h	940/940
	Outdoor		2,380/2,080
Net Dimension H×W×D Net Weight	Indoor	mm	198×900×620
		kg(lbs)	23 (51)
	Outdoor	mm	632×799×290
		kg(lbs)	36 (79)
Piping Connections (Small / Large)		mm	6.35/12.70
Drain Pipe Diameter (I.D./O.D.)			25/32
Max Pipe Length (Pre-Charge)		m	25 (15)
Max Height Difference			15
Operation Range	Cooling	°CDB	-10 to 46
	Heating	CDB	-15 to 24
Refrigerant			R410A

024

 \odot

۲

۲

Selectable with a wide range of static pressure

By using the DC fan motor, it is possible to change the static pressure range from 0 to 90 Pa. The change of static pressure range is possible by remote controller.

۲

۲



Drain pump is standard accessory It allows flexible installation.



Drain hose is standard accessory

Auto Louver Grille Kit (Option)

Simple flat Auto Louver will provide comfort airflow and harmonize with luxury interior.



Dimensions Models: ARYG18LLTB

۲

*Service accessibility must be allowed for when installing the product. Please consult the installation manual for the necessary service access size.

Wide operation range



Optional parts

Wired Remote Controller:	UTY-RNNYM
Simple Remote Controller:	UTY-RSNYM
Wireless LAN Interface	UTY-TFNXZ3
External Connect Kit:	UTD-ECS5A
Auto Louver Grille Kit:	UTD-GXSB-W
IR Receiver Unit:	UTY-LRHYM
Remote Sensor Unit:	UTY-XSZX

(Unit : mm)

74

774 52 30 (Bolt pitch) 377 50 30 P100x8=800 850 934 (Bolt pitch) 167 119 89 55 198 168 78 20 69 850 144 900 263 371 620

 (\bullet)

۲

025

s WD